SPESIFIKASI PEMBELIAN PERALATAN KAMERA DAN AKSESORI UNTUK KEGUNAAN FAMA TV

| Butiran / Spesifikasi | Kuantiti | Harga/unit (RM) | Jumlah Harga (RM) |
|---|---|--|---|
| Kamera DSLR + Battery + Memory Card | 1 | | |
| Fast 0.02-sec AF, with 425 phase-detection AF points Real-time Tracking and Real-time Eye AF, to detect and hold onto moving subjects 5-axis optical image stabilisation for rocksolid shooting 24.2-megapixel APS-C Exmor™ CMOS image sensor | | | |
| recording, with diverse movie features 64gb Memory Card | | | |
| Kamera Lens 18mm-135 | 1 | | |
| MINIMUM FOCUS DISTANCE 0.45 m (1.48 ft) | | | |
| MAXIMUM MAGNIFICATION RATIO (X) 0 29 | | | |
| FILTER DIAMETER (MM) 55 | | | |
| WEIGHT | | | |
| 325 g (11.5 oz.) Flash Light HVL | 1 | | |
| 2.4 GHz Radio Transceiver with 98' Range Compatible with Sony ADI / P-TTL Guide Number: 197' at ISO 100 and 105mm Zoom Range: 20-200mm (14mm with Panel) Quick Shift Bounce for 90° L/R Pivot Tilts from -8 to 150° Wireless TTL Ratio Controller/Remote LED Light and AF Illuminator Quick Navi Interface with Dot Matrix LCD | | | |
| | Fast 0.02-sec AF, with 425 phase-detection AF points Real-time Tracking and Real-time Eye AF, to detect and hold onto moving subjects 5-axis optical image stabilisation for rocksolid shooting 24.2-megapixel APS-C Exmor™ CMOS image sensor High-resolution 4K HDR (HLG) movie recording, with diverse movie features 64gb Memory Card Kamera Lens 18mm-135 MINIMUM FOCUS DISTANCE 0.45 m (1.48 ft) MAXIMUM MAGNIFICATION RATIO (X) 0 29 FILTER DIAMETER (MM) 55 WEIGHT 325 g (11.5 oz.) Flash Light HVL • 2.4 GHz Radio Transceiver with 98' Range • Compatible with Sony ADI / P-TTL • Guide Number: 197' at ISO 100 and 105mm • Zoom Range: 20-200mm (14mm with Panel) • Quick Shift Bounce for 90° L/R Pivot Tilts from -8 to 150° • Wireless TTL Ratio Controller/Remote LED Light and AF Illuminator | Card Fast 0.02-sec AF, with 425 phase-detection AF points Real-time Tracking and Real-time Eye AF, to detect and hold onto moving subjects 5-axis optical image stabilisation for rocksolid shooting 24.2-megapixel APS-C Exmor™ CMOS image sensor High-resolution 4K HDR (HLG) movie recording, with diverse movie features 64gb Memory Card Kamera Lens 18mm-135 MINIMUM FOCUS DISTANCE 0.45 m (1.48 ft) MAXIMUM MAGNIFICATION RATIO (X) 0 29 FILTER DIAMETER (MM) 55 WEIGHT 325 g (11.5 oz.) Flash Light HVL 2.4 GHz Radio Transceiver with 98' Range Compatible with Sony ADI / P-TTL Guide Number: 197' at ISO 100 and 105mm Zoom Range: 20-200mm (14mm with Panel) Quick Shift Bounce for 90° L/R Pivot Tilts from -8 to 150° Wireless TTL Ratio Controller/Remote LED Light and AF Illuminator Quick Novi Interface with Dot Matrix LCD | Tast 0.02-sec AF, with 425 phase-detection AF points Real-time Tracking and Real-time Eye AF, to detect and hold onto moving subjects 5-axis optical image stabilisation for rock- solid shooting 24.2-megapixel APS-C Exmor™ CMOS image sensor High-resolution 4K HDR (HLG) movie recording, with diverse movie features 64gb Memory Card Kamera Lens 18mm-135 MINIMUM FOCUS DISTANCE 0.45 m (1.48 ft) MAXIMUM MAGNIFICATION RATIO (X) 0 29 FILTER DIAMETER (MM) 55 WEIGHT 325 g (11.5 oz.) Flash Light HVL 1 2.4 GHz Radio Transceiver with 98' Range Compatible with Sony ADI / P-TTL Guide Number: 197' at ISO 100 and 105mm Zoom Range: 20-200mm (14mm with Panel) Quick Shift Bounce for 90° L/R Pivot Tilts from -8 to 150° Wireless TTL Ratio Controller/Remote LED Light and AF Illuminator Quick Navi Interface with Dot Matrix LCD |

| 3. | Bateri Kamera | 1 | |
|----|--|---|--|
| | The 7.2 VDC, 2280mAh NP-FZ100 Rechargeable Lithium-Ion Battery from Sony is a high-capacity Z- series power source for select digital cameras. This battery has InfoLITHIUM support for displaying the remaining charge of the battery on the camera's LCD screen. | | |
| 4. | Panoramic Background 4m (13') (Chromakey Green) | 1 | |
| | The Panoramic is a collapsible 4m (13') wide, 2.3m (7'5") high background that folds down neatly into its own carry case and fits easily into a car. Weighing only 9kg (19.8lb) it's ideal for busy imagemakers on the move. The background is completely self-supporting and can be set up in minutes. The structure comprises three individual aluminium framed sections, connected together with a hinge clip to allow the background to be set up flat to lean against a wall or with the side frames folded in to create a wraparound effect. The Chroma Key Green cover just simply clips to the aluminium frame and creates a taught, seamless surface. | | |
| 5. | TRIPOD and Head | 2 | |
| | Made from aluminum alloy, measures 3.74" high and provides a bubble level and precision control handle. Wide platform fluid pan video | | |
| | head ideal for HDSLR cameras | | |
| | 5.3 lb pre-set spring-loaded counterbalance system | | |
| | Side-lock system for easier and safer camera mounting | | |
| | Aluminum alloy construction | | |
| | Includes long quick-release plate | | |
| | | | |
| | | | |

operating the VL Series via

Separate Controller and Adapter from the light body:Though VL Series have high power output (150W, 200W & 300W)?the VL Series

introducesnew design which

maintains them very compact and lightweight aircraft bodies. VL150 weighs just 1.97kg and even the

Bluetooth.

| | VL300 weights 2.64kg. With a separated controller, users will be able to mount the light in any position and which has a crystal clear LCD panel. | | | |
|-----|---|---|--|--|
| | · | | | |
| 7. | Light Stand | 2 | | |
| | Type: 1/4 Screw Photography tripod stand Color: Black Material: Aluminum Locking Collar & steel tubes Sections: 3 Diameter: 25mm/30mm/35mm Max. tube diameter: 35mm Max. load: 9kg / 19.8lb Max. height: 280cm / 9ft Folded height: 93cm / 3.ft Package size: 98 * 9 * 9cm / 40 * 3.5 * 3.5in Package weight: 1700g / | | | |
| 8. | V Mount Battery DC Charger | 2 | | |
| | Adapter Specification: Input: DC 16.8V/5A(Max) Output: D-Tap 1: 14.8V/10A(Max) D-Tap 2: 14.8V/10A(Max) USB 1: 5V/2.1A USB 2: 5V/2.1A Dimenion: 100.8 x 128 x 56mm Model: MBP-120 | | | |
| 9. | Rotating Display | 1 | | |
| | Stand 100KG loadable Ф42cm 360°turning 2 speeds model turntable with remote controller #420 (White) | | | |
| 10. | Rotating Display | 1 | | |
| | Stand 50KG loadable Ф42cm 360° turning 2 speeds model turntable with remote controller #420 (Black) | | | |
| 11. | Rotating Display | 1 | | |
| | Stand 50KG heavy loadable Ф320 mm 360°turning 2 speeds 2 directions 4 angles model turntable #320 (White) | | | |
| | JUMLAH | | | |
| | SST% | | | |
| | | | | |